

# SwiftReader X

Cutting Edge Video Intercom and Access

Model: SL-SRX-1



SwiftReader X is designed to provide a visually stunning and intuitive video intercom and access control experience. It brings a number of innovative new features to provide a fully customizable solution for occupant and visitor access control in condominiums, apartment buildings, office buildings, gated communities, and industrial buildings.

## AT A GLANCE

- Face recognition touchless door access
- Virtual passes and temporary visitor access
- PIN based access (Unique pin per user)
- Mobile door access
- Multi-tenant video intercom
- Package and food delivery access
- Video calls over the mobile app

## FEATURES

|                  |                                                                                   |
|------------------|-----------------------------------------------------------------------------------|
| Credential Types | Face Recognition Access, Mobile App Access, BLE, NFC, PIN Unlock, Key Card Access |
| Camera           | 1/2.8" Sensor, 1080p, FOV 115°(H)/ 63°V                                           |
| Audio            | 2 Speaker, Dual Microphone Array with Echo cancellation                           |
| Display          | 8" IPS LCD, Touchscreen enabled                                                   |

## Communications

|                    |                           |
|--------------------|---------------------------|
| Wireless Standards | BLE, NFC                  |
| Internet           | Ethernet. Cat5e or higher |
| Reader Frequency   | 13.56 MHz                 |

## Environmental

|                       |             |
|-----------------------|-------------|
| Operating Temperature | -22°F 140°F |
| Operating Humidity    | 10 90%      |

## Inputs, Output and Power

|                    |                 |
|--------------------|-----------------|
| Power Requirements | 24 VDC, 2.5A    |
| Relays             | 3 Output Relays |
| Inputs             | 3 Inputs        |

## Mechanical

|                          |                                        |
|--------------------------|----------------------------------------|
| Mounting Options         | Flush mounted and wall mounted         |
| Flush Mounted Dimensions | 13.78 (H) x 5.12 (W) x 1.64 (D) inches |
| Wall Mounted Dimensions  | 13.78 (H) x 5.12 (W) x 2.13 (D) inches |

## Certifications and Warranty

|                |                                                  |
|----------------|--------------------------------------------------|
| Certifications | FCC Part 15                                      |
| Ratings        | IP65, IK10                                       |
| Warranty       | 2-year limited warranty on electronic components |

